

Muurame storage furniture



Materials

- pull-out drawer
 - color white (code 00): fronts MDF, sides membrane-coated furniture board, base HDF (see explanation of types of board at the bottom of the product sheet)
 - color high gloss white (codes OW, OWW, WW) and ultramarine (code MM): fronts MDF, sides solid wood, base plywood
 - color oak (code TT): fronts MDF, sides solid wood, base plywood
- steel pull-out drawer runners
- frame: membrane-coated furniture board, oak veneer
- board materials formaldehyde class E1 (100 g dry board contains less than 8 mg formaldehyde)
- the wood is produced in Europe (oak)
- glass doors Moduli, Mup and Ikoni: toughened 6 mm glass, edges beveled and ground shiny
- glass doors Nappi and Neppari: untoughened 6 mm glass, edges beveled and ground shiny
- glass shelf Moduli, Mup and Ikoni: toughened 8 mm glass, edges beveled and ground shiny
- glass shelf Nappi and Neppari: toughened 6 mm glass, edges beveled and ground shiny
- acrylic door Nappi and Neppari: 6 mm cast acrylic board, beveled edges
- Mup, Moduli and Ikoni framed door's acrylic: 4 mm cast acrylic board
- Moduli, Mup and Ikoni board shelf maximum weight evenly loaded: 25 kg
- Moduli glass shelf maximum weight evenly loaded: 411/38 kg, 406/40 kg, 409/23 kg
- Mup glass shelf maximum weight evenly loaded: 466/40 kg, 476/30 kg, 496/20 kg, 465/25 kg, 495/15 kg
- Ikoni glass shelf maximum weight evenly loaded: 561/28 kg, 562/20 kg, 563/12 kg
- Nappi: maximum weight evenly loaded, 15 kg on board/glass shelf
- Neppari: maximum weight evenly loaded, 10 kg on board/glass shelf

Surface treatment

- white 00: 3-component catalyzed paint, special characteristic non-yellowing*
- high gloss white WW: polyurethane paint
- oak TT: acrylic varnish, contains 2% white paste
- ultramarine MM: polyurethane paint and/or lacquer

Care instructions

- Wipe using a neutral (pH 6-8) cleaning liquid (e.g. washing up liquid) on a damp cloth after which the surface should be dried
- dark marks caused by sharp objects (e.g. rings, watches) on white catalyzed coated surfaces (color 00) can usually be removed either using an eraser, a cloth soaked in a mild detergent or with a damp sponge, e.g. Vileda MiracleClean or equivalent.

We retain the right to make changes.

MDF: Medium Density Fiber Board (Raw material dense-grained softwood chips and sawdust, density 690 kg/m³) HDF: High Density Fiber Board (Raw material dense-grained softwood and sawdust, density 900 kg/m³) Furniture board: P2 strength class (EN312 standard, classification P1-P7), raw materials wood chips and sawdust

* The strength of the paint used by Muurame is its excellent ability to prevent yellowing, i.e. the surface remains pure white for an exceptionally long time despite exposure to sunlight. However, the stronger the surface required, the harder it is to prevent yellowing. The type of paint used seeks to obtain an optimum result regarding preventing yellowing and surface hardness.